

FILTER UNIT



For adsorption of moisture, solid and gaseous decomposition products

B077R22

Portable pre-filter unit (p_e 50 bar)

Dry filters filled with molecular sieve and aluminium oxide Al₂O₃ combined with particle filter

For adsorption of oil-aerosols, moisture and gaseous or dusty decomposition products

B071R22

Portable separating filter unit (p_e 50 bar)

Separating filters filled with activated carbon granulates and aluminium oxide Al₂O₃ combined with particle filter



Technical data:

Dimensions: 30.7" L x 8.3" W x 7.9" H (780 mm x 210 mm x 200 mm)
Weight: 29.8 lbs (13,5 kg)

Standard equipment:

2 DILO coupling groove parts DN20 at the filter unit
Particle filters
Dry filter (water absorption capacity: 175 g at a dew point of -36 °C)
Safety valve (p _e 50 bar)
Gauge
Operating manual

Optional accessories at an extra charge:

2 meter long rubber hose DN20 with coupling tongue part on both ends	6-1017-R020
5 meter long rubber hose DN20 with coupling tongue part on both ends	6-1017-R050
2 meter long wire braided hose DN20 with coupling tongue part on both ends PN 50 bar	6-1365-R020
5 meter long wire braided hose DN20 with coupling tongue part on both ends PN 50 bar	6-1365-R050
Spare filter cartridge (for dry filter B077R22)	B077-10
Spare filter cartridge activated carbon / Al ₂ O ₃ for B071R22	B071-30
Spare filter cartridge (for particle filter B077R22 / B071R22)	B077-06
Operating manual	6-0004-R213