



DN20 V3

This practical adapter kit contains DILO DN20 transition pieces for the most commonly used SF₆ gas compartment connections. The self-sealing couplings ensure that no SF₆ is released into the atmosphere during coupling and uncoupling.



Technical Data:

| | |
|---------------------------------|---|
| Case dimensions: | 25" L x 19.50" W x 11" D (635 mm x 495.3 mm x 279.4 mm) |
| Case weight: | 48.50 lbs. (22 kgs) |
| Shipping dimensions and weight: | 25.50" L x 20" W x 11.50" D (648 mm x 508 mm x 292 mm) |

Fittings Included in Kit:

QTY

| | | | QTY |
|----|----------------------------|--|-----|
| 1 | VK/BG-03/20-CGA590 | DILO DN20 self-sealing male (M45x2) to CGA590 with DILO ball valve | 1 |
| 2 | 6-1281-R001 | DILO DN20 self-sealing female (M45x2) with air filter <i>*for gas compartment venting with air</i> | 1 |
| 3 | 3-401-R002 E | DILO DN20 self-sealing male (M45x2) to 1" male NPT | 1 |
| 4 | VK/A-02/20-3-1037-R001 | DILO DN20 self-sealing male (M45x2) to 1/4" female NPT | 1 |
| 5 | VK/A-02/20-3-1037-R002 | DILO DN20 self-sealing male (M45x2) to 3/8" female NPT | 1 |
| 6 | 6-1059-R011 | DILO DN20 self-sealing (M45x2 to M45x2) **Hose Union** | 1 |
| 7 | 6-1161-R012 | DILO DN20 self-sealing female (M45x2) to (Type 21) male quick connect | 1 |
| 8 | 3-893-R006 | DILO DN20 self-sealing male with 90-degree bend to Malmquist (ASEA) | 1 |
| 9 | 6-1027-R001 | DILO DN20 self-sealing male (M45x2) to 1 1/4" female JIC flare | 1 |
| 10 | 6-1092-R007 | DILO DN20 self-sealing male to DILO DN8 self-sealing female adapter | 1 |
| 11 | DILO Safety Glasses | Protective eyewear for when working with high pressure systems | 2 |
| 12 | 05-0061-R004 | Yellow plastic cover for DILO DN20 (M45x2) female couplings | 10 |
| 13 | 05-0581-R002 | White plastic cover for DILO DN20 (M45x2) male couplings | 10 |
| 14 | 14' Logo Adapter Kit Strap | 14' Ratchet Strap / 1" width / for securing cylinders on the jobsite | 2 |